

TECH
QUIP



AMI
ADVANCED MICRO INSTRUMENTS

MODEL 210BX
PERCENT
OXYGEN

UNMATCHED PERFORMANCE FOR PERCENT OXYGEN MONITORING

The **MODEL 210BX** is AMI's most advanced Percent Oxygen Analyzer. It combines patented technologies and superior design to deliver unmatched performance, reliability and ease of use.

PATENTED ELIMINATOR CELL BLOCK™

The patented design offers the most efficient gas path in the industry by combining all of the critical sample handling components, including a flow meter, metering valve, 3-way gas control valve, sensor pocket and pressure sensor, into one solid cross drilled block. Sample gas only needs to travel 4 inches before reaching the sensor, resulting in a 400% faster response time.

DESIGNED FOR THE USER

This virtually maintenance-free Analyzer with front-loading O₂ sensor, intuitive controls and compact size make installation, maintenance and operation of the **MODEL 210BX** the easiest of any Percent Oxygen Analyzer in its class.

PROPRIETARY O₂ SENSOR TECHNOLOGY

AMI's patented **P Series** oxygen sensors deliver extremely fast response, high reliability and long life. Every sensor undergoes a battery of tests in our factory to guarantee that they meet our strict quality and performance standards. Our **P Series** percent oxygen sensors are designed to enhance the superior performance of the **MODEL 210BX** Analyzer.

FULL SUITE OF STANDARD FEATURES

The **MODEL 210BX** comes standard with advanced features, including dual independent alarms, comprehensive alarm logic (fail safe or non-fail safe, latching or non-latching and independent alarm delays), alarm bypass and 3 levels of security settings. Automatic data logging provides detailed time-stamped records of O₂ measurement, gas pressure, temperature, supply voltage and power brown-out history.

COMMON APPLICATIONS

- ▶ NATURAL GAS
- ▶ AIR SEPARATION
- ▶ AEROSPACE

MODEL 210B



PHYSICAL & ELECTRICAL SPECIFICATIONS

WEIGHT	MOUNTING	GAS CONNECTIONS	WETTED PARTS
16.0 lbs (7.26 kg)	Wall Mount or 2.0" Pipe	¼" 316 S.S. compression fittings	316 S.S. fittings, electro-less nickel-plated cell block, gold-plated contacts, acrylic flow meter & O-rings (Viton, kalrez, and Buna-N)
POWER			
DC		AC	
10 – 24 VDC, 150 mA max (non-heated) 10 – 24 VDC, 2.2 Amps max (heated)		100 – 240 VAC, 150 mA max (non-heated) 100 – 240 VAC, 550 mA max (heated)	



Note: 2-year Warranty for Parts & Labor for any defects in materials or workmanship. 6-month Warranty for oxygen sensors

OPERATIONAL SPECIFICATIONS

OUTPUT RANGES			AMBIENT OPERATIONAL TEMPERATURE			FLOW RATE (RECOMMENDED)	INLET GAS PRESSURE	OPERATIONAL ALTITUDE	
STANDARD RANGE (USER SELECTABLE)	OPTIONAL RANGES (USER SELECTABLE) LOW HIGH		NON-HEATED	HEATED	HEATED WITH EXTREME WEATHER ENCLOSURE			DC	AC
0 – 1.0%	0 – 1000 ppm	0 – 10.0%	25°F to 115°F (–3.9°C to 46°C)	–20°F to 115°F (–29°C to 46°C)	–40°F to 115°F (–40°C to 46°C)	0.1 to 2.0 SCFH (0.05 – 1.0 Lpm)	0.5 – 150 psig (0.03 – 10.3 bar)	≤ 5,500 m (18,000 ft)	≤ 2,500 m (8,200 ft)
0 – 5.0%	0 – 1.0%	0 – 25.0%							
0 – 10.0%	0 – 10.0%	0 – 50.0%							
0 – 25.0%	0 – 25.0%	0 – 100.0%							

SENSOR & ANALYZER PERFORMANCE SPECIFICATIONS

P-2 SENSOR	P-3 SENSOR	P-4 SENSOR	P-5 SENSOR	REPEATABILITY	APPROVALS
Max Range: 0–50% 90% upscale response: 8 sec Special Conditions: O ₂ in inert gas	Max Range: 0–25% 90% upscale response: 30 sec Special Conditions: Up to 50% CO ₂	Max Range: 0–100% 90% upscale response: 30 sec Special Conditions: Enriched Oxygen	Max Range: 0–25% 90% upscale response: 30 sec Special Conditions: <500 ppm H ₂ S, Up to 50% CO ₂	±1% of range or ±0.1% of oxygen, whichever is greater ACCURACY ±1% of full scale range at constant conditions	Class I, Division 1, Groups B,C,D, T4 Class I Zone 0/1, AEx ia/db IIB+H2 T4 Ga/Gb IECEX: Ex ia IIB+H2 T4 Ga/Ex db IIB+H2 T4 Gb UKCA/PESO: Ex ia/db IIB+H2 T4 Ga/Gb ATEX: II 1/2 G Ex ia/db IIB+H2T4 Ga/Gb Ingressed Protection: IP65

ANALYZER KEY FEATURES

ELIMINATOR CELL BLOCK™	Contains a Complete Sample System with all components, including the flow meter, metering valve, pressure sensor and 3-way Selection (Sample/Span/Off) Valve, fully integrated
ALARMS	2 fully adjustable concentration alarms with configurable Alarm logic and Relay Contacts, featuring: <ul style="list-style-type: none"> ▶ Alarm Bypass ▶ Alarm Delays ▶ Trigger Above or Below Setpoint ▶ Latching/Non-latching ▶ Failsafe/Non-failsafe ▶ Open or Close on Alarm
INTERNAL PRESSURE SENSOR	Measures gas inlet pressure from 0 – 150 psig.
ANALOG OUTPUTS	1 – 5 VDC and 4 – 20mA isolated output signals and Modbus bi-directional RS485 communication
COMMAND CENTER	Software that works across AMI's Analyzers and gives users access to advanced functions: <ul style="list-style-type: none"> ▶ Error Status Display ▶ Data Logger (records O₂ measurements, temperature, psig, and power) ▶ Alarm Configurations ▶ Calibration Details
ACCESSORIES	<ul style="list-style-type: none"> ▶ Demister ▶ LRP ▶ Extreme Weather Enclosure